

Model Rocket SAFETY CODE

*This official Model Rocketry Safety Code has been developed and promulgated by the National Association of Rocketry.
(Basic Version, Effective February 10, 2001)*

1. MATERIALS. I will use only lightweight, non-metal parts for the nose, body and fins of my rocket.

2. MOTORS. I will use only certified, commercially-made rocket motors, and will not tamper with these motors or use them for any purposes except those recommended by the manufacturer.

3. IGNITION SYSTEM. I will launch my rockets with an electrical launch system and electrical motor igniters. My launch system will have a safety interlock in series with the launch switch, and will use a launch switch that returns to the "off" position when released.

4. MISFIRES. If my rocket does not launch when I press the button of my electrical launch system, I will remove the launcher's safety interlock or disconnect its battery, and will wait 60 seconds after the last launch attempt before allowing anyone to approach the rocket.

5. LAUNCH SAFETY. I will use a countdown before launch, and will ensure that everyone is paying attention and is a safe distance of at least 15 feet away when I launch rockets with D motors or smaller, and 30 feet when I launch larger rockets. If I am uncertain about the safety or stability of an untested rocket, I will check the stability before flight and will fly it only after warning spectators and clearing them away to a safe distance.

6. LAUNCHER. I will launch my rocket from a launch rod, tower, or rail that is pointed to within 30 degrees of the vertical to ensure that the rocket flies nearly straight up, and I will use a blast deflector to prevent the motor's exhaust from hitting the ground. To prevent accidental eye injury, I will place launchers so that the end of the launch rod is above eye level or will cap the end of my launch rod when it is not in use.

7. SIZE. My model rocket will not weigh more than 1500 grams (53 ounces) at liftoff and will not contain more than 125 grams (4.4 ounces) of propellant or 320N-sec (71.9 pound-seconds) of total impulse. If my model rocket weighs more than one pound (453 grams) at liftoff or has more than 4 ounces (113grams) of propellant, I will check and comply with Federal Aviation Administration regulations before flying.

8. FLIGHT SAFETY. I will not launch my rocket at targets, into clouds or near airplanes, and will not put any flammable or explosive payload in my rocket.

9. LAUNCH SITE. I will launch my rocket outdoors, in an open area at least as large as shown in the accompanying table, and in safe weather conditions with wind speeds no greater than 20 miles per hour. I will ensure that there is no dry grass close to the launch pad, and that the launch site does not present risk of grass fires.

Installed Total Impulse (N-sec)	Equivalent Motor Types	Minimum Site Dimensions (ft)
0.00 - 1.25	1/4A, 1/2A	50
2.26 - 2.50	A	100
2.51 - 5.00	B	200
5.01 - 10.00	C	400
10.01 - 20.00	D	500
20.01 - 40.00	E	1,000
40.01 - 80.00	F	1,000
80.01 - 160.00	G	1,000
160.01 - 320.00	Two G's	1,500

10. RECOVERY SYSTEM. I will use a recovery system such as a streamer or parachute in my rocket so that it returns safely and undamaged and can be flown again, and I will use only flame-resistant or fireproof recovery system wadding in my rocket.

11. RECOVERY SAFETY. I will not attempt to recover my rocket from power lines, tall trees, or other dangerous places.